



First Advance 10 kW; N° Série 03-20-000--

Red Pod – the soul of fire

www.red-pod.com mail@red-pod.com

N° DOP DD-049-B

Emissions (13%O₂):

	Nom	Part
CO :	300 mg/m ³	-
NOx :	200 mg/m ³	-
OGC :	60 mg/m ³	-
PM :	20 mg/m ³	-

Performance:

	Nom	Part
P :	10,3 kW	-
P _W :	-	-
P _{SH} :	10,3 kW	-
η :	91 %	-
p :	12 Pa	-

EN 16510-1:2022 / EN 16510-2-6:2022

Flue gas outlet temperature (Nom-Part):	176 °C - -
Diameter of the flue gas outlet :	80 mm
Fire safety of installation to the chimney :	T 200 G
Seasonal space heating efficiency (η _s) :	79 %
Energy Efficiency Index (EEI) :	119
Energy Efficiency Class :	A+
The permissible maximum water operation pressure (P _W - bar):	-
Protective Insulation according to manufacture r's instructions :	-
Power supply voltage (E) :	230 V
Power supply frequency (f) :	50 Hz
Maximum electric power input (W _{max}) :	378 W
Mass of the appliance (m) :	89 kg
Fuel Type :	Type L
Operation Type :	CON - Continuous

Minimum distances to combustibile materials

Bottom d _B = 0 mm	Floor d _F = 1500 mm
Ceiling d _C = 1500 mm	Rear d _R = 300 mm
Front d _P = 2000 mm	Side d _S = 500 mm
Non-Comb d _{non} = -	

Side radiation area d_L = 1500 mm