



PS109; N° Série 03-20-00---

Red Pod – the soul of fire
www.red-pod.com mail@red-pod.com

N° DOP DD-066-A

Emissions (13%O ₂):			Performance:		
	Nom	Part		Nom	Part
CO :	300 mg/m ³	-	P :	8,8 kW	-
NOx :	200 mg/m ³	-	P _W :	-	-
OGC :	60 mg/m ³	-	P _{SH} :	8,8 kW	-
PM :	20 mg/m ³	-	η :	91 %	-
			p :	12 Pa	-

EN 16510-1:2022 / EN 16510-2-6:2022

Flue gas outlet temperature (Nom-Part):	198 °C - -
Diameter of the flue gas outlet :	80 mm
Fire safety of installation to the chimney :	T 200 G
Seasonal space heating efficiency (η _s) :	79 %
Energy Efficiency Index (EEI) :	120
Energy Efficiency Class :	A+
The permissible maximum water operation pressure (P _W - bar):	-
Protective Insulation acording to manufacture r's instructions :	-
Power supply voltage (E) :	230 V
Power supply frequency (f) :	50 Hz
Maximum electric power input (W _{max}) :	378 W
Mass of the appliance (m) :	61 kg
Fuel Type :	Type L
Operation Type :	CON - Continuous

Minimum distances to combustibile materials

Bottom d _B = 0 mm	Floor d _F = 1500 mm	Side radiation area d _L = 1500 mm
Ceiling d _C = 1500 mm	Rear d _R = 300 mm	
Front d _P = 1000 mm	Side d _S = 500 mm	
Non-Comb d _{non} = -		

